

Package: mailtoR (via r-universe)

October 7, 2026

Type Package

Title Creates a Friendly User Interface for Emails Sending in 'shiny'

Version 0.1.0

Maintainer Mohamed El Fodil Ihaddaden <ihaddaden.fodeil@gmail.com>

Description Allows the user to generate a friendly user interface for emails sending. The user can choose from the most popular free email services ('Gmail', 'Outlook', 'Yahoo') and his default email application. The package is a wrapper for the 'Mailtoui' 'JavaScript' library. See <<https://mailtoui.com/#menu>> for more information.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Imports htmltools, glue, utils

RoxygenNote 7.1.0

URL <https://github.com/feddelegrand7/mailtoR>

BugReports <https://github.com/feddelegrand7/mailtoR/issues>

Repository <https://feddelegrand7.r-universe.dev>

Date/Publication 2020-12-09 21:55:47 UTC

RemoteUrl <https://github.com/feddelegrand7/mailtoR>

RemoteRef HEAD

RemoteSha a5c0a486cef9e05ab7cc4d14f5b25cd76e5595b3

Contents

mailtoR	2
use_mailtoR	3
Index	4

`mailtoR`*Create a friendly user interface for sending emails*

Description

Create a friendly user interface for sending emails

Usage

```
mailtoR(email, text, subject = NULL, cc = NULL, bcc = NULL, body = NULL)
```

Arguments

<code>email</code>	the emails of the recipients
<code>text</code>	the link text that will be displayed on the ui
<code>subject</code>	the subject of the email. Defaults to NULL
<code>cc</code>	the emails of the CC (carbon copy) recipients. Defaults to NULL
<code>bcc</code>	the emails of the BCC (blind carbon copy) recipients. Defaults to NULL
<code>body</code>	the body of the email. Defaults to NULL

Value

a user interface for sending emails

Examples

```
if (interactive()) {

  ui <- fluidPage(

    mailtoR(email = "",
            text = "click here to send an email"),
    use_mailtoR()

  )

  server <- function(input, output){

  }

  shinyApp(ui, server)
```

```
}
```

`use_mailtoR`*Enable the MailtoUI javascript library*

Description

The function activates the capabilities of the MailtoUI javascript library. The user needs to set it at the end of the shiny ui.

Usage

```
use_mailtoR()
```

Value

called for the side effect of activating the MailtoUI library

Examples

```
# Put the function at the bottom of the ui

use_mailtoR()
```

Index

`mailtoR`, [2](#)

`use_mailtoR`, [3](#)