

Package: ralger (via r-universe)

October 10, 2026

Type Package

Title Easy Web Scraping

Version 2.3.0

Maintainer Mohamed El Fodil Ihaddaden <ihaddaden.fodeil@gmail.com>

Description The goal of 'ralger' is to facilitate web scraping in R.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

URL <https://github.com/feddelegrand7/ralger>

BugReports <https://github.com/feddelegrand7/ralger/issues>

VignetteBuilder knitr

Imports rvest, xml2, tidyr, dplyr, stringr, robotstxt, crayon, curl,
stringi, urltools (>= 1.7.3), purrr (>= 1.0.2)

Suggests knitr, testthat, rmarkdown, covr

RoxygenNote 7.3.1

Config/pak/sysreqs libicu-dev libxml2-dev libssl-dev

Repository <https://feddelegrand7.r-universe.dev>

Date/Publication 2026-03-14 12:18:58 UTC

RemoteUrl <https://github.com/feddelegrand7/ralger>

RemoteRef HEAD

RemoteSha 84d9a2a15ddf43660f81859f76f467324b898ee4

Contents

attribute_scrap	2
audio_scrap	3
colors_scrap	4
comments_scrap	4
csv_scrap	5

images_noalt_scrap	6
images_preview	6
images_scrap	7
paragraphs_scrap	8
pdf_scrap	9
scrap	9
table_scrap	10
tidy_scrap	11
titles_scrap	11
weblink_scrap	12
xls_scrap	13
xlsx_scrap	13

Index	15
--------------	-----------

attribute_scrap	<i>Scraping attributes from HTML elements</i>
-----------------	---

Description

This function is used to scrape attributes from HTML elements

Usage

```
attribute_scrap(link, node, attr, askRobot = FALSE)
```

Arguments

link	the link of the web page to scrape
node	the HTML element to consider
attr	the attribute to scrape
askRobot	logical. Should the function ask the robots.txt if we're allowed or not to scrape the web page ? Default is FALSE.

Value

a character vector.

Examples

```
# Extracting the web links within the World Bank research and publications page

link <- "https://ropensci.org/"

# scraping the class attributes' names from all the anchor

attribute_scrap(link = link, node = "a", attr = "class")
```

audio_scrap*Scrape Audio Files from a Web Page*

Description

This function is used to scrape audio file URLs from a web page and optionally download them. It searches both <audio> tags and <a> (anchor) tags for links matching the specified audio extensions.

Usage

```
audio_scrap(link, extensions = c("mp3", "wav"), path = getwd(), askRobot = FALSE)
```

Arguments

link	the link of the web page to scrape
extensions	a character vector of audio file extensions to filter by (without the leading dot). Defaults to c("mp3", "wav").
path	the path where audio files will be downloaded. Defaults to the current working directory. Set to NULL to return URLs without downloading.
askRobot	logical. Should the function ask the robots.txt if we're allowed or not to scrape the web page? Default is FALSE.

Value

called for the side effect of downloading audio files. Returns the vector of matched audio URLs invisibly, or NULL if none are found.

Examples

```
## Not run:

# Scrape and download mp3 and wav files from a page
audio_scrap(
  link = "https://www.example.com/podcasts",
  extensions = c("mp3", "wav"),
  path = getwd()
)

# Return audio URLs without downloading
audio_scrap(
  link = "https://www.example.com/podcasts",
  extensions = "mp3",
  path = NULL
)

## End(Not run)
```

colors_scrap

Scrape Color Codes from a Web Page

Description

This function scrapes all color codes present within a given website. It searches inline style attributes, <style> tags, and linked external CSS stylesheets for color values in the following formats: hexadecimal (#RGB, #RRGGBB, #RRGGBBAA), rgb(), rgba(), hsl(), and hsla().

Usage

```
colors_scrap(link, askRobot = FALSE)
```

Arguments

link	the link of the web page to scrape. Can be a character vector of multiple URLs.
askRobot	logical. Should the function ask the robots.txt if we're allowed or not to scrape the web page? Default is FALSE.

Value

a character vector of unique color codes found on the page, or invisible(NULL) if none are found, or NA on error.

Examples

```
colors_scrap(link = "https://ropensci.org/")
```

comments_scrap*Scrape HTML comments from a web page*

Description

Extracts HTML comments (<!-- comment -->) from a webpage. Useful for detecting hidden notes, debug info, or developer messages.

Usage

```
comments_scrap(link, askRobot = FALSE)
```

Arguments

link	Character. The URL of the web page to scrape.
askRobot	Logical. Should the function check robots.txt before scraping? Default is FALSE.

Value

A character vector of HTML comments found on the page.

Examples

```
link <- "https://example.com"
comments_scrap(link)
```

csv_scrap	<i>Scrape and download CSV files from a Web Page</i>
-----------	--

Description

Scrape and download CSV files from a Web Page

Usage

```
csv_scrap(link, path = getwd(), askRobot = FALSE)
```

Arguments

link	the link of the web page
path	the path where to save the CSV files. Defaults to the current directory
askRobot	logical. Should the function ask the robots.txt if we're allowed or not to scrape the web page ? Default is FALSE.

Value

called for the side effect of downloading CSV files from a website

images_noalt_scrap	<i>Scrape Images URLs that don't have 'alt' attributes</i>
--------------------	--

Description

Scrape Images URLs that don't have 'alt' attributes

Usage

```
images_noalt_scrap(link, askRobot = FALSE)
```

Arguments

link	the URL of the web page
askRobot	logical. Should the function ask the robots.txt if we're allowed or not to scrape the web page ? Default is FALSE.

Value

a character vector of images' URL without "alt" attribute

Examples

```
images_noalt_scrap(link = "https://www.r-consortium.org/")
```

images_preview	<i>Scrape Images URLs</i>
----------------	---------------------------

Description

Scrape Images URLs

Usage

```
images_preview(link, askRobot = FALSE)
```

Arguments

link	the link of the web page
askRobot	logical. Should the function ask the robots.txt if we're allowed or not to scrape the web page ? Default is FALSE.

Value

Images URLs

Examples

```
images_preview(link = "https://posit.co/")
```

images_scrap	<i>Scrape Images from a Web Page</i>
--------------	--------------------------------------

Description

Scrape Images from a Web Page

Usage

```
images_scrap(link, imgpath = getwd(), extn, askRobot = FALSE)
```

Arguments

link	the link of the web page
imgpath	the path of the images. Defaults to the current directory
extn	the extension of the image: png, jpeg ...
askRobot	logical. Should the function ask the robots.txt if we're allowed or not to scrape the web page ? Default is FALSE.

Value

called for the side effect of downloading images

Examples

```
## Not run:  
  
images_scrap(link = "https://posit.co/", extn = "jpg")  
  
## End(Not run)
```

paragraphs_scrap	<i>Website text paragraph scraping</i>
------------------	--

Description

This function is used to scrape text paragraphs from a website.

Usage

```
paragraphs_scrap(  
  link,  
  contain = NULL,  
  case_sensitive = FALSE,  
  collapse = FALSE,  
  askRobot = FALSE  
)
```

Arguments

link	the link of the web page to scrape
contain	filter the paragraphs according to the character string provided.
case_sensitive	logical. Should the contain argument be case sensitive ? defaults to FALSE
collapse	if TRUE the paragraphs will be collapsed into one element and the contain argument ignored.
askRobot	logical. Should the function ask the robots.txt if we're allowed or not to scrap the web page ? Default is FALSE.

Value

a character vector.

Examples

```
# Extracting the paragraphs displayed on the health page of the New York Times  
  
link    <- "https://www.nytimes.com/section/health"  
  
paragraphs_scrap(link)
```

pdf_scrap

*Scrape and download pdf files from a Web Page***Description**

Scrape and download pdf files from a Web Page

Usage

```
pdf_scrap(link, path = getwd(), askRobot = FALSE)
```

Arguments

link	the link of the web page
path	the path where to save the PDF files. Defaults to the current directory
askRobot	logical. Should the function ask the robots.txt if we're allowed or not to scrape the web page ? Default is FALSE.

Value

called for the side effect of downloading PDF files from a website

scrap

*Simple website scraping***Description**

This function is used to scrape one element from a website.

Usage

```
scrap(link, node, clean = FALSE, askRobot = FALSE)
```

Arguments

link	the link of the web page to scrape
node	the HTML or CSS element to consider, the SelectorGadget tool is highly recommended
clean	logical. Should the function clean the extracted vector or not ? Default is FALSE.
askRobot	logical. Should the function ask the robots.txt if we're allowed or not to scrape the web page ? Default is FALSE.

Value

a character vector

Examples

```
# Extracting imdb top 250 movie titles
link <- "https://www.imdb.com/chart/top/"
node <- "h3.ipc-title__text"
scrap(link, node)
```

table_scrap	<i>HTML table scraping</i>
-------------	----------------------------

Description

This function is used to scrape an html table from a website.

Usage

```
table_scrap(link, choose = 1, header = TRUE, askRobot = FALSE)
```

Arguments

link	the link of the web page containing the table to scrape
choose	an integer indicating which table to scrape
header	do you want the first line to be the leader (default to TRUE)
askRobot	logical. Should the function ask the robots.txt if we're allowed or not to scrape the web page ? Default is FALSE.

Value

a data frame object.

Examples

```
# Extracting premier ligue 2019/2020 top scorers

link <- "https://www.topscorersfootball.com/premier-league"
table_scrap(link)
```

tidy_scrap	<i>Website Tidy scraping</i>
------------	------------------------------

Description

This function is used to scrape a tibble from a website.

Usage

```
tidy_scrap(link, nodes, colnames, clean = FALSE, askRobot = FALSE)
```

Arguments

link	the link of the web page to scrape
nodes	the vector of HTML or CSS elements to consider, the SelectorGadget tool is highly recommended.
colnames	the names of the expected columns.
clean	logical. Should the function clean the extracted tibble or not ? Default is FALSE.
askRobot	logical. Should the function ask the robots.txt if we're allowed or not to scrape the web page ? Default is FALSE.

Value

a tidy data frame.

Examples

```
# Extracting imdb movie titles and rating
link    <- "https://www.imdb.com/chart/top/"
my_nodes <- c("a > h3.ipc-title__text", "span.ratingGroup--imdb-rating")
names   <- c("title", "rating")
tidy_scrap(link, my_nodes, names)
```

titles_scrap	<i>Website title scraping</i>
--------------	-------------------------------

Description

This function is used to scrape titles (h1, h2 & h3 html tags) from a website. Useful for scraping daily electronic newspapers' titles.

Usage

```
titles_scrap(link, contain = NULL, case_sensitive = FALSE, askRobot = FALSE)
```

Arguments

link	the link of the web page to scrape
contain	filter the titles according to a character string provided.
case_sensitive	logical. Should the contain argument be case sensitive ? defaults to FALSE
askRobot	logical. Should the function ask the robots.txt if we're allowed or not to scrape the web page ? Default is FALSE

Value

a character vector

Examples

```
# Extracting the current titles of the New York Times

link    <- "https://www.nytimes.com/"

titles_scrap(link)
```

weblink_scrap	<i>Website web links scraping</i>
---------------	-----------------------------------

Description

This function is used to scrape web links from a website.

Usage

```
weblink_scrap(link, contain = NULL, case_sensitive = FALSE, askRobot = FALSE)
```

Arguments

link	the link of the web page to scrape
contain	filter the web links according to the character string provided.
case_sensitive	logical. Should the contain argument be case sensitive ? defaults to FALSE
askRobot	logical. Should the function ask the robots.txt if we're allowed or not to scrape the web page ? Default is FALSE.

Value

a character vector.

Examples

```
# Extracting the web links within the World Bank research and publications page

link <- "https://www.worldbank.org/en/research"

weblink_scrap(link)
```

xls_scrap

Scrape and download Excel xls files from a Web Page

Description

Scrape and download Excel xls files from a Web Page

Usage

```
xls_scrap(link, path = getwd(), askRobot = FALSE)
```

Arguments

link	the link of the web page
path	the path where to save the Excel xls files. Defaults to the current directory
askRobot	logical. Should the function ask the robots.txt if we're allowed or not to scrape the web page ? Default is FALSE.

Value

called for the side effect of downloading Excel xls files from a website

xlsx_scrap

Scrape and download Excel xlsx files from a Web Page

Description

Scrape and download Excel xlsx files from a Web Page

Usage

```
xlsx_scrap(link, path = getwd(), askRobot = FALSE)
```

Arguments

link	the link of the web page
path	the path where to save the Excel xlsx files. Defaults to the current directory
askRobot	logical. Should the function ask the robots.txt if we're allowed or not to scrape the web page ? Default is FALSE.

Value

called for the side effect of downloading Excel xlsx files from a website

Examples

```
## Not run:
```

```
xlsx_scrap(  
link = "https://www.rieter.com/investor-relations/results-and-presentations/financial-statements"  
)
```

```
## End(Not run)
```

Index

attribute_scrap, [2](#)
audio_scrap, [3](#)

colors_scrap, [4](#)
comments_scrap, [4](#)
csv_scrap, [5](#)

images_noalt_scrap, [6](#)
images_preview, [6](#)
images_scrap, [7](#)

paragraphs_scrap, [8](#)
pdf_scrap, [9](#)

scrap, [9](#)

table_scrap, [10](#)
tidy_scrap, [11](#)
titles_scrap, [11](#)

weblink_scrap, [12](#)

xls_scrap, [13](#)
xlsx_scrap, [13](#)