

Package: rfold (via r-universe)

August 20, 2024

Type Package

Title Working with many R Folders Within an R Package

Version 0.2.0

Description Allows developers to work with many R folders inside a package. It offers functionalities to transfer R scripts (saved outside the R folder) into the R folder while making additional checks.

License MIT + file LICENSE

Encoding UTF-8

URL <https://github.com/feddelegrand7/rfold>

BugReports <https://github.com/feddelegrand7/rfold/issues>

Imports cli (>= 3.6.1), fs (>= 1.5.0), glue, here (>= 1.0.1), usethis (>= 2.0.1)

RoxygenNote 7.1.1

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

Repository <https://feddelegrand7.r-universe.dev>

RemoteUrl <https://github.com/feddelegrand7/rfold>

RemoteRef HEAD

RemoteSha b4886f77fbc066951e4a019f9270dd081802e6d5

Contents

| | |
|-----------------|----------|
| rfold | 2 |
| Index | 3 |

| | |
|-------|---|
| rfold | <i>Transfer .R files into the R directory</i> |
|-------|---|

Description

Transfer .R files into the R directory

Usage

```
rfold(folders_to_ignore = NULL, script_name_prefix = "DO_NOT_EDIT_")
```

Arguments

`folders_to_ignore`

a string vector of plain names folders that should be ignored where transferring .R files into the main R folder (for example a dev folder). Defaults to NULL

`script_name_prefix`

characters string of length 1 that will be appended to the start of the .R scripts when transferring them to the R folder. Defaults to 'DO_NOT_EDIT', set it to NULL for no appending

Value

called for the side effect of transferring all R files

Index

rfold, [2](#)