

# Package: rintimg (via r-universe)

October 11, 2026

**Type** Package

**Title** View Images on Full Screen in 'RMarkdown' Documents and 'shiny' Applications

**Version** 0.1.0

**Maintainer** Mohamed El Fodil Ihaddaden <ihaddaden.fodeil@gmail.com>

**Description** Allows the user to view an image in full screen when clicking on it in 'RMarkdown' documents and 'shiny' applications. The package relies on the 'JavaScript' library 'intense-images'. See <<https://tholman.com/intense-images/>> for more information.

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** true

**Imports** htmltools, glue

**RoxygenNote** 7.1.1

**URL** <https://github.com/feddelegrand7/rintimg>

**BugReports** <https://github.com/feddelegrand7/rintimg/issues>

**Repository** <https://feddelegrand7.r-universe.dev>

**Date/Publication** 2025-04-07 15:15:33 UTC

**RemoteUrl** <https://github.com/feddelegrand7/rintimg>

**RemoteRef** HEAD

**RemoteSha** 9f6b43d00a7403532e2a5a16f2b1bfb25ec90e3e

## Contents

|                              |          |
|------------------------------|----------|
| img_intensify . . . . .      | 2        |
| intense_dependency . . . . . | 3        |
| <b>Index</b>                 | <b>4</b> |

---

`img_intensify`*Viewing images on full screen*

---

**Description**

Viewing images on full screen

**Usage**

```
img_intensify(target = "img")
```

**Arguments**

|                     |                                                                                                              |
|---------------------|--------------------------------------------------------------------------------------------------------------|
| <code>target</code> | By default, the function intensifies all the images (<img> tag) however the user can target specific classes |
|---------------------|--------------------------------------------------------------------------------------------------------------|

**Value**

images that when clicked can be viewed on full screen no matter their initial size

**Examples**

```
if (interactive()) {  
  
  ui <- fluidPage(  
  
    h1("Click on the image to view it in full screen"),  
  
    img(src = "https://www.r-project.org/logo/Rlogo.png",  
        width = "200px", height = "200px"),  
  
    img_intensify()  
  
  )  
  
  server <- function(input, output) {  
  
  }  
  
  shinyApp(ui = ui, server = server)  
  
}
```

---

|                                 |                                                        |
|---------------------------------|--------------------------------------------------------|
| <code>intense_dependency</code> | <i>Create an HTML dependency for intense-images.js</i> |
|---------------------------------|--------------------------------------------------------|

---

**Description**

Create an HTML dependency for intense-images.js

**Usage**

`intense_dependency()`

# Index

`img_intensify`, [2](#)  
`intense_dependency`, [3](#)